

OrbWeave 20 is a multi-layer reinforced 10oz geomembrane ideal for medium and heavy-duty applications. OrbWeave 20 is the industry leader in quality and strength. An extremely chemical and puncture resistant geomembrane with light weight HDPE woven skrim core with OrbWeave technology.









HIGH STRENGTH

HIGH PUNCTURE

UV RESISTANT

RECYCLEABLE

Applications:

- Landfill/Temp rain covers
- Grain covers
- Athletic field covers
- Drainage canals

- Turf underlayment
- Stockpile covers
- Medium duty liners
- **Environmental production**
- Spill containment
- Rail car liners
- And more

Features/Benefits:

- 144" rolls allow it to be factory fabricated to reduce field seaming and installation time.
- Allows for larger fabricated panels.
- Puncture & abrasion resistant construction
- Woven core provides excellent dimensional stability
- Excellent UV, ozone & oxidation resistance
- Available in white and other colors upon request
- 10 year exposed or 20 year buried warranty





Physical Properties & Testing Data:

| OrbWeave 20 | | |
|--------------------------|-------------|-----------------------------|
| Property | Performance | Value |
| Thickness | ASTM D1777 | 20mil |
| Coating Thickness | | 2.75mil |
| Color (others available) | | BLK/BLK |
| Grab Tensile | ASTM D7004 | MD 250 lbs TD 340 lbs |
| Tongue Tear | ASTM D5884 | MD 89 lbs TD 85 lbs |
| Hydrostatic Conductivity | MVTR | 1.97x10 ⁻¹² cm/s |
| Mullen Burst | ASTM D751 | 550psi |
| Puncture Resistance | ASTM D4833 | 171lbs |
| Carbon Black Content | ASTM D4218 | 3.6% |
| Weathering | ASTM G151 | >90% after 2,000 hrs |

MD= Machine Direction; TD= Transverse Direction

These values are typical data and not intended for limiting specifications. We believe them to be reliable and accurate to the best of our ability and are intended for guidelines of performance (+/- 10%)

